

PTFE ADDITIVE POWDER

ChemWatch Review SDS

Version No: 4.5

Safety Data Sheet (Conforms to Regulation (EC) No 2015/830)

Chemwatch Hazard Alert Code: 1

Issue Date: **29/05/2017** Print Date: **29/05/2017** S.REACH.GBR.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product Identifier	
Product name	PTFE ADDITIVE POWDER
Chemical Name	Polytetrafluoroethylene
Synonyms	INOLUB™ T100, 200, 300 SERIES. R 600, 700, 800 SERIES
Chemical formula	(C2F4)x
Other means of identification	Not Available
CAS number	9002-84-0*
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Relevant identified uses	Additive
Uses advised against	Not Applicable
I.3. Details of the supplier of Registered company name	
Address	12/ A Dahej Indus trial Estate GIDC
Telephone	+91-2641-618333
Fax	+91-2641-618012
Website	www.inolub.com
Email	inolub@gfl.co.in
I.4. Emergency telephone nu	ımber
Association / Organisation	Gujarat Fluorochemicals Itd
Emergency telephone numbers	+91-2641-618080-81
Other emergency telephone	Not Available

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Not considered a hazardous substance according to Reg. (EC) No 1272/2008 and its amendments. Not classified as Dangerous Goods for transport purposes.

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	1	
Toxicity	0	0 = Minimum
Body Contact	0	2 = Moderate
Reactivity	1	3 = High
Chronic	0	4 = Extreme

Classification according to regulation (EC) No [1]	Not Applicable
--	----------------

2.2. Label elements

CLP label elements	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

Not Applicable

Supplementary statement(s)

Not Applicable

Version No: 4.5 Page 2 of 10 Issue Date: 29/05/2017

PTFE ADDITIVE POWDER

Print Date: 29/05/2017

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

2.3. Other hazards

Cumulative effects may result following exposure*.

Limited evidence of a carcinogenic effect*.

REACh - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP]
1.9002-84-0 2.Not Available 3.Not Available 4.Not Available	>99.9	polytetrafluoroethylene	Not Applicable

1. Classified by Chemwatch; 2. Classification drawn from EC Directive 67/548/EEC - Annex I; 3. Classification drawn from EC Directive 1272/2008 - Annex VI 4. Legend: Classification drawn from C&L

3.2.Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

In case of burns:

- Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth.
- DO NOT remove or cut away clothing over burnt areas
 which has adhered to the skin as

this can cause further injury.

DO NOT break blister or remove solidified material.

- Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain.
- For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth.
- DO NOT apply ointments, oils, butter, etc. to a burn under any circumstances
- Water may be given in small quantities if the person is conscious.
- Alcohol is not to be given under any circumstances.
- Reassure.
- Treat for shock by keeping the person warm and in a lying position.

Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arri val of the patient.

For thermal burns:

Decontaminate area around burn.

Consider the use of cold packs and topical antibiotics.

For first-degree burns (affecting top layer of skin)

- ▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.
- Use compresses if running water is not available
- Cover with sterile non-adhesive bandage or clean cloth.

Do NOT apply butter or ointments; this may cause infection.

Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.

For second-degree burns (affecting top two layers of skin)

- Cool the burn by immerse in cold running water for 10-15 minutes.
- Use compresses if running water is not available.
- Do NOT apply ice as this may lower body temperature and cause further damag e.
- Do NOT break blisters or apply butter or ointments; this may cause infection.

Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape. To prevent shock: (unless the person has a head, neck, or leg inj ury, or it would cause discomfort):

- Lav the person flat.
- Elevate feet about 12 inches.
- Elevate burn area above heart level, if possible.
- Cover the person with coat or blanket.

Seek medical assistance.

For third-degree burns Seek immediate medical or emergency assistance.

In the mean time:

Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not I eave lint in wound. Separate burned toes and fingers with dry, ster ile dressings.

DO NOT pull away clothing

Version No: 4.5 Page 3 of 10 Issue Date: 29/05/2017 Print Date: 29/05/2017

PTFE ADDITIVE POWDER

Do not soak burn in water or apply ointments or butter; this may cause infection. To prevent shock see above. For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. Have a person with a facial burn sit up. Check pulse and breathing to monitor for shock until emergency help arrives. If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel, For THERMAL burns: Do NOT remove contact lens Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye. Seek urgent medical assistance, or transport to hospital If dust is inhaled, remove from contaminated area, Encourage patient to blow nose to ensure clear breathing passages. Ask patient to rinse mouth with water but to not drink water. Seek immediate medical attention. Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by **Eve Contact** skilled personnel. For THERMAL burns: Do NOT remove contact lens Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye. Seek urgent medical assistance, or transport to hospital. If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. In case of burns: Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth. DO NOT remove or cut away clothing over burnt areas. DO NOT pull away clothing which has adhered to the skin as this can cause further injury. DO NOT break blister or remove solidified material Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain. For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth. DO NOT apply ointments, oils, butter, etc. to a burn under any circumstances Water may be given in small quantities if the person is conscious. Alcohol is not to be given under any circumstances. Treat for shock by keeping the person warm and in a lying position. Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arri val of the patient. For thermal burns: Decontaminate area around burn. ▶ Consider the use of cold packs and topical antibiotics. For first-degree burns (affecting top layer of skin) ▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides. Use compresses if running water is not available. Cover with sterile non-adhesive bandage or clean cloth. Do NOT apply butter or ointments; this may cause infection. Skin Contact ▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur. For second-degree burns (affecting top two layers of skin) Cool the burn by immerse in cold running water for 10-15 minutes. Use compresses if running water is not available. Do NOT apply ice as this may lower body temperature and cause further damage. Do NOT break blisters or apply butter or ointments; this may cause infection. ▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape. To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort): Lay the person flat. Elevate feet about 12 inches. Elevate burn area above heart level, if possible. Cover the person with coat or blanket. Seek medical assistance. For third-degree burns Seek immediate medical or emergency assistance. In the mean time: Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not I eave lint in wound. Separate burned toes and fingers with dry, sterile dressings. Do not soak burn in water or apply ointments or butter; this may cause infection. To prevent shock see above. For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. Have a person with a facial burn sit up. Check pulse and breathing to monitor for shock until emergency help arrives. If dust is inhaled, remove from contaminated area. Encourage patient to blow nose to ensure clear breathing passages. Inhalation Ask patient to rinse mouth with water but to not drink water.

4.2 Most important symptoms and effects, both acute and delayed

Ingestion

Seek immediate medical attention. Immediately give a glass of water.

First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Version No: 4.5 Page 4 of 10 Issue Date: 29/05/2017 Print Date: 29/05/2017

PTFE ADDITIVE POWDER

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media

- Do NOT direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.
- Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

5.2. Special hazards arising from the substrate or mixture

bility	Incompatil	Fire
--------	------------	------

F Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlori ne bleaches, pool chlorine etc. as ignition may result

5.3. Advice for firefighters

J.J. Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	 Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions. Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in a ir or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions). Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any
	source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagati on of an explosion. Combustion products include:, carbon monoxide (CO), carbon dioxide (CO2), hydrogen fluoride, other pyrolysis products typical of burning
	organic material CARE: Contamination of heated / molten liquid with water may cause violent steam explosion, with scattering of hot contents.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment and dust 	Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use dry clean up procedures and avoid generating dust.
	Major Spills	Alert Fire Brigade and tell them location and nature of hazard.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling	 The greatest potential for injury caused by molten materials occurs during purging of machinery (moulders, extruders etc.) It is essential that workers in the immediate area of the machinery wear eye and skin protection (such as full face, safety glasses, heat resistant gloves, overalls and safety boots) as protection from thermal burns. Fumes or vapours emitted from hot melted materials, during converting operations, may condense on overhead metal surfaces or exhaust ducts. The condensate may contain substances which are irritating or toxic. Avoid contact of that material with the s kin. Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with incompatible materials. Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in a ir or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions) Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.
Fire and explosion protection	See section 5

Version No: **4.5** Page **5** of **10** Issue Date: **29/05/2017**

PTFE ADDITIVE POWDER

Print Date: 29/05/2017

Other information

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry area protected from environmental extremes.
- Store away from incompatible materials and foodstuff containers.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container

Lined metal can, lined metal pail/

seed. For saturated perfluorocarbons:

- can. Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.

Storage incompatibility

Avoid contamination of water, foodstuffs, feed or

Standard oxidation-reduction potentials do not apply to PFCs. The materials are unaffected by electrochemical reactions and do

- not dissociate in aqueous media.

 They are essentially already fully oxidised and are unaffected by standard oxidizing agents such as permanganates, chromates, etc. The only
- known oxidation takes place only at high temperatures by thermal decomposition. Likewise, the materials are only reduced under extreme conditions, requiring reducing agents such as elemental
- sodium Avoid magnesium, aluminium and their alloys, brass and steel.

For polytetrafluoroethylene (PTFE) and other related polyfluorinated pol ymers:

Avoid storage with strong oxidising agents, tetrafluoroethylene, hexafluoroethylene, perfluoroisobutylene, carbonyl fluoride and hydrogen fluoride.

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
polytetrafluoroethylene	Polytetrafluoroethylene	0.3 mg/m3	3.3 mg/m3	20 mg/m3
Ingredient	Original IDLH	Revised IDLH		
polytetrafluoroethylene	Not Available	Not Available		

8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high I evel of protection. The basic types of engineering controls are:

8.2.1. Appropriate engineering controls

protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that

strategically "adds" and "removes" air in the work environment.

For molten materials:

Provide mechanical ventilation; in general such ventilation should be provided at compounding/ converting areas and at fabricating/ filling work stations where the material is heated. Local exhaust ventilation should be used over and in the vicinity of machinery involved in handling the molten material. Keep dry!!

Processing temperatures may be well above boiling point of water, so wet or damp material may cause a serious steam explosion if used in unvented equipment.

8.2.2. Personal protection









Eye and face protection

- Safety glasses with side
- shields Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be crea ted for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the m aterial, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calc ulated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be o

Hands/feet protection

bserved when making a final choice. Personal hygiene is a key element of effective hand care.

- When handling hot materials wear heat resistant, elbow length gloves.
- Rubber gloves are not recommended when handling hot objects, materials
- Protective gloves eg. Leather gloves or gloves with Leather facing

Page 6 of 10 Version No: 4.5 Issue Date: 29/05/2017 Print Date: 29/05/2017

PTFE ADDITIVE POWDER

	Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry soli ds, where abrasive particles are not present. • polychloroprene. • nitrile rubber. • butyl rubber.
Body protection	See Other protection below
Other protection	 When handling hot or molten liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. Usually handled as molten liquid which requires worker thermal protection and increases hazard of vapour exposure. CAUTION: Vapours may be irritating. No special equipment needed when handling small quantities. OTHERWISE: Overalls. Barrier cream. Eyewash unit.
Thermal hazards	Not Available

Respiratory protection

Type A -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A P1 Air-line*	-	A PAPR -P1
up to 50 x ES	Air-line**	A P2	A PAPR -P2
up to 100 x ES	-	A P3	-
		Air-line*	-
100+ x ES	-	Air-line**	A PAPR -P3

^{* -} Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyan ide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methy I bromide, AX = Low boiling point organic compounds(below 65 degC)

For molten

materials: 76a-p()

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequenc y and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or d istress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit te sted as part of a complete respiratory protection program.
- ▶ Use approved positive flow mask if significant quantities of dust becomes
- airborne. Try to avoid creating dust conditions.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance I	White powder	·	
Physical state	Solid	Relative density (Water = 1)	2.14-2.20
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	320-342	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available

Issue Date: 29/05/2017 Version No: 4.5 Page 7 of 10 Print Date: 29/05/2017

PTFE ADDITIVE POWDER

Vapour density (Air = 1) Not Available VOC g/L Not Available

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. At temperatures of over 400 deg. C the polymer begins to decompose with the reaction becoming faster as temperature rises. Fumes from burning materials containing PTFE irritate the upper airway and may be harmful if exposure is prolonged. Overheated or burnt PTFE releases hydrogen fluoride (a highly irritating and corrosive gas) and small amounts of carbonyl fluoride (highly toxic). Processing for an overly long time or processing at overly high temperatures may cause generation and release of highly irrit ating vapours, which irritate eyes, nose, throat, causing red itching eyes, coughing, sore throat.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be u sed in an occupational setting. Molten material is capable of causing burns.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may caus e transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. This material contains a substantial amount of polymer considered to be of low concern. These are classified under having MWs of between 1000 to 10000 with less than 25% of molecules with MWs under 1000 and less than 10% under 500; or having a molecular weight average of over 10000. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessme nt.

PTFE MICROPOWDER	TOXICITY	IRRITATION	
	Not Available	Not Available	
	TOXICITY	IRRITATION	
polytetrafluoroethylene	Oral (rat) LD50: 1250 mg/kg [2]		
	Nil reported * [Manufacturer]		
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless		

otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

POLYTETRAFLUOROETHYLENE

Perfluorinated compounds are potent peroxisome proliferators.

The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa.

The substance is classified by IARC as Group 3: **NOT** classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

X – Data available but does not fill the criteria for classification

— Data required to make classification available

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source

Version No: 4.5 Page 8 of 10

PTFE ADDITIVE POWDER

Issue Date: **29/05/2017**Print Date: **29/05/2017**

		I	T.		T .
polytetrafluoroethylene	LC50	96	Fish	64.087mg/L	3
polytetrafluoroethylene	EC50	96	Algae or other aquatic plants	248.438mg/L	3
polytetrafluoroethylene	EC50	384	Crustacea	15.096mg/L	3
	Extracted from 1 IIIC	LID Toxicity Data 2 Europe ECHA	Pagistared Substances - Ecotoxicological Int	formation - Aquatic Toxicity 2	EDIM/INI Quito 1/2 12

Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. E CETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -

For polytetrafluoroethylene (PTFE) and other related polyfluorinated polymers:

Ecotoxicity is expected to be low based on the near zero water solubility of the polymer. Material is considered inert and is not expeced ted to e biodegradable or toxic.

Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

12.2. Persistence and degradability

Ingredient	Persistence: Water/ Soil	Persistence: Air
polytetrafluoroethylene	HIGH	HIGH

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
etrafluoroethylene	LOW (LogKOW = 1.2142)

12.4. Mobility in soil

Legend:

Ingredient	Mobility	
polytetrafluoroethylene	LOW (KOC = 106.8)	

12.5.Results of PBT and vPvB assessment

	Р	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product / Packaging disposal	 DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1.UN number	Not Applicable			
14.2.UN proper shipping name	Not Applicable	Not Applicable		
14.3. Transport hazard class(es)	Class Not Applicable Subrisk Not Applicable			
14.4.Packing group	Not Applicable			
14.5.Environmental hazard	Not Applicable			
14.6. Special precautions for user	Hazard identification (Kemler) Classification code Hazard Label Special provisions Limited quantity	Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable		

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable

Version No: 4.5 Page 9 of 10 Issue Date: 29/05/2017
Print Date: 29/05/2017

PTFE ADDITIVE POWDER

14.2. UN proper shipping name Not Applicable ICAO/IATA Class Not Applicable 14.3. Transport hazard ICAO / IATA Subrisk Not Applicable **ERG Code** Not Applicable 14.4. Packing group Not Applicable 14.5. Environmental hazard Not Applicable Not Applicable Special provisions Not Applicable Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Not Applicable 14.6. Special precautions for Passenger and Cargo Packing Instructions Not Applicable Passenger and Cargo Maximum Qty / Pack Not Applicable Passenger and Cargo Limited Quantity Packing Instructions Not Applicable Passenger and Cargo Limited Maximum Qty / Pack Not Applicable

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	IMDG Class Not Applicable IMDG Subrisk Not Applicable	
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number Not Applicable	
	Special provisions Not Applicable	
	Limited Quantities Not Applicable	

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable			
14.2. UN proper shipping name	Not Applicable	Not Applicable		
14.3. Transport hazard	Not Applicable Not	Not Applicable Not Applicable		
class(es)	Not Applicable			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	i i			
	Classification code	Not Applicable		
	Special provisions	Not Applicable		
14.6. Special precautions for user	Limited quantity	Not Applicable		
	Equipment required	Not Applicable		
	Fire cones number	Not Applicable		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

POLYTETRAFLUOROETHYLENE(9002 -84-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

European Customs Inventory of Chemical Substances ECICS (English)

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chai n if available.

ECHA SUMMARY

Ingredient CAS number Index No ECHA Dossier

Version No: **4.5** Page **10** of **10** Issue Date: **29/05/2017**

PTFE ADDITIVE POWDER

Print Date: 29/05/2017

polytetrafluoroethylene	9002-84-0 Not	Available Not Av	railable
Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Not Classified	GHS07, Wng	H319, H315, H335, H332
2	Not Classified, Eye Irrit. 2, Skin Irrit. 2, STOT SE 3	GHS07, Wng	H319, H315, H335, H332
Harmonisation Code 1 = T	The most prevalent classification. Harmonisation Code 2 = Th	e most sev ere classification.	
National Inventory	Status		
Acceptable AIOO	V		

National Inventory	Status	
Australia - AICS	Υ	
Canada - DSL	Υ	
Canada - NDSL	N (polytetrafluoroethylene)	
China - IECSC	Υ	
Europe - EINEC / ELINCS / NLP	N (polytetrafluoroethylene)	
Japan - ENCS	Υ	
Korea - KECI	Υ	
New Zealand - NZIoC	Υ	
Philippines - PICCS	Υ	
USA - TSCA	Υ	
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	s)

SECTION 16 OTHER INFORMATION

Full text Risk and Hazard codes

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as in dependent review by the Chemwatch

 ${\it Classification\ committee\ using\ available\ literature\ references}.$

A list of reference resources used to assist the committee may be found at: $\underline{\text{www.chemwatch.net}}$

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro -organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

 ${\sf PC-TWA: Permissible \ Concentration-Time \ Weighted \ Average}$

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit 。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Li mit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as per mitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.