





# **TECHNICAL DATA SHEET**

#### **TECHNICAL INFORMATION**

INOLUB® T320F is a PTFE micropowder with discrete particles and "best in class" powder flow. INOLUB® T320F is one of our most versatile products and can be used in a wide range of applications as an additive at concentrations in the range of 1-20%.

## **FEATURES AND BENEFITS**

- Low friction and squeak
- Excellent wear resistance
- Improved stain resistance and soil release
- Improved pressure velocity limits
- Discrete particles, providing minimal rheological impact

# **PROPERTIES**

Properties	Test Method	Unit	Nominal Value
Appearance	-	-	White free flowing powder
Bulk Density	ASTM D4894	g/l	350
Mean particle size (D50)	ASTM D4894	μm	20
Specific surface area	Nitrogen Adsorption	m²/g	<3
Melting point	ASTM D4894	°C (°F)	326 (619)

Note: These are typical properties and not to be used for specification purposes.

## TYPICAL END USE APPLICATIONS

INOLUB® T320F used in polymers to reduce friction and wear, and to improve non-stick performance.

#### FDA/EU STATEMENT

INOLUB® T320F meets the compositional requirement of Food and Drug Administration (FDA) regulation 21C.F.R.177.1550, and EU food contact regulation 10/2011. A detailed statement is available upon request.

Updated on: 18.12.2023 Page 1 of 2

# **INOLUB® T320F**

## **PACKAGING**

INOLUB® T320F is available in 25 kg corrugated boxes, packed in a green colored polyethylene liner.

#### **STORAGE**

INOLUB® T320F may be stored indefinitely, provided that the packaging remains unopened and that it has been stored in a clean and dry area.

# SAFETY AND HANDLING

Although INOLUB® T320F presents no safety hazard under normal handling conditions, please refer to the Material Safety Data Sheet to avoid potential hazards before processing.

INOLUB® is the brand name of Gujarat Fluorochemicals Limited (GFL) used for its brand of fluoropolymer additives. INOLUB® can be used in applications duly approved by GFL. Customers who plan to use the word INOLUB® as the trademark on or relation to their manufactured parts and other products in any style or combination or any manner whatsoever must contact GFL for prior permission for such use. No consumer/user of GFL fluoropolymer additives is permitted to claim that their products contain INOLUB® without prior permission from GFL.

The information provided in the bulletin is furnished at no cost to the recipient and is based on the information and technical data that Gujarat Fluorochemicals Limited believes is correct and sound. Those who choose to use the information must be technically qualified, and do so entirely at their own cost and risk. The users must determine and ensure that their specific conditions of processing present no health or safety hazards. GFL does not warranty, either expressly or impliedly in respect of the use of this information for application of its INOLUB® branded fluoropolymer additives and shall bear no liability as a result of any loss or damage caused directly or indirectly due to use of any information provided in this bulletin. Nothing contained herein can be taken or construed as a grant of license by GFL to operate under or a recommendation to infringe any patents.

WARNING: Do not use any of INOLUB® PTFE additives in medical devices that are designed for permanent implantation in the human body. For other medical uses, prior permission of GFL may be sought.

# SALES AND TECHNICAL SUPPORT

# **Corporate & Marketing office:**Gujarat Fluorochemicals Limited

Inox Towers, Plot no. 17, Sector 16/A Noida-202301, U.P., INDIA Tel: +91-120-6149600 Fax: +91-120-6149610

#### Europe

Gujarat Fluorochemicals GmbH

Esplanade 40, 9<sup>th</sup> Floor 20354 Hamburg, Germany +49 40 5582 395 - 80

# Works

#### **Gujarat Fluorochemicals Limited**

12/A, GIDC Dahej Industrial Estate.
Tehsil- Vagra, Distt. Bharuch-392230, Gujarat, INDIA Website: www.fluonox.co.in; www.gfl.co.in
Email: contact@gfl.co.in

#### **Americas**

GFL Americas, LLC

1212 Corporate Dr., Suite-540, Irving, TX 75038, USA +1 512 446 7700



Updated on: 18.12.2023 Page 2 of 2